

Cruagh Dining Set – Assembly Instructions

List of parts & fixings

- 1 x Table Top
- 4 x Seat Tops
- 2 x Table Leg Sections
- 8 x Seat Leg Sections
- 4 x Table Leg End Rails
- 16 x Seat Braces
- 2 x Shelf Supports
- 2 x Shelf Boards
- 32 x 60mm Green Screws
- 62 x 90mm Green Screws



When assembling, loosely fix together until fully assembled then tighten all the fixings.

We recommend gluing all mortice and tenon joints before fully assembling. (Glue not provided)

ASSEMBLING THE TABLE SECTION

1. Firstly, assemble leg sections.
2. Using the end rails, slot into top and bottom of the mortice hole in the pre-assembled leg section. Fix using 90mm screws through pre-drilled holes in the leg section repeat for all sides.
3. Now you have assembled the table leg sections, place the table top upside down on a level surface making sure not to scratch the table top. Screw down assembled leg section using 90mm screws provided, making sure there is an even space around table top.
4. Upright table and screw shelf supports into desired position on the legs at both ends, next fix boards on using 60mm screws provided. Now fix 485mm table brace through pre-drilled holes using 60mm screws provided.

NEXT ASSEMBLE THE SEAT SECTIONS

5. First, assemble leg sections.
6. Using the end rails, slot into top and bottom of the mortice hole in the pre-assembled leg section. Fix using 80mm screws through pre-drilled holes in the leg section repeat for all sides.
7. Now you have assembled the Seat leg sections, place the seat top upside down on a level surface making sure not to scratch the table top. Screw down assembled leg section using 90mm screws provided, making sure there is an even space around table top. (Approximately 115mm from leg to end of table top.) Now fix 220mm seat brace through pre-drilled holes using 60mm screws provided (as shown in the picture).



IMPORTANT CUSTOMER INFORMATION

To minimise twisting and warping all garden furniture products should only be used on firm level ground. Softwood is a natural material which can twist and split during periods of wet/dry, hot/cold weather. If cracks do appear it is a natural occurrence and not a fault with the product or material. The best way to treat this is to use a cloth and rub a little PVA wood glue into the crack and once dry sand the area lightly. This will not affect the treatment of the product.